

AASHTO Elements, Defects, and Condition States (2015 Interims)

Decks / Slabs (NBEs)		
El. No.	Element Name	Units
12	Reinforced Concrete Deck	AREA (sq. ft.)
13	Prestressed Concrete Deck	AREA (sq. ft.)
15	Prestressed Concrete Top Flange	AREA (sq. ft.)
16	Reinforced Concrete Top Flange	AREA (sq. ft.)
28	Steel Deck with Open Grid	AREA (sq. ft.)
29	Steel Deck with Concrete Filled Grid	AREA (sq. ft.)
30	Steel Deck Corrugated/Orthotropic/Etc.	AREA (sq. ft.)
31	Timber Deck	AREA (sq. ft.)
38	Reinforced Concrete Slab	AREA (sq. ft.)
54	Timber Slab	AREA (sq. ft.)
60	Other Deck	AREA (sq. ft.)
65	Other Slab	AREA (sq. ft.)

Bridge Railings (NBEs)		
El. No.	Element Name	Units
330	Metal Bridge Railing	LENGTH (ft.)
331	Reinforced Concrete Bridge Railing	LENGTH (ft.)
332	Timber Bridge Railing	LENGTH (ft.)
333	Other Bridge Railing	LENGTH (ft.)
334	Masonry Bridge Railing	LENGTH (ft.)

Joints (BMEs)		
El. No.	Element Name	Units
300	Strip Seal Expansion Joint	LENGTH (ft.)
301	Pourable Joint Seal	LENGTH (ft.)
302	Compression Joint Seal	LENGTH (ft.)
303	Assembly Joint with Seal	LENGTH (ft.)
304	Open Expansion Joint	LENGTH (ft.)
305	Assembly Joint without Seal	LENGTH (ft.)
306	Other Joint	LENGTH (ft.)

Approach Slabs (BMEs)		
El. No.	Element Name	Units
320	Prestressed Concrete Approach Slab	AREA (sq. ft.)
321	Reinforced Concrete Approach Slab	AREA (sq. ft.)

Wearing Surface and Protective Systems (BMEs)		
El. No.	Element Name	Units
510	Wearing Surfaces	AREA (sq. ft.)
515	Steel Protective Coating	AREA (sq. ft.)
520	Concrete Reinforcing Steel Protective System	AREA (sq. ft.)
521	Concrete Protective Coating	AREA (sq. ft.)

Superstructures (NBEs)		
El. No.	Element Name	Units
102	Steel Closed Web/Box Girder	LENGTH (ft.)
104	Prestressed Concrete Closed Web/Box Girder	LENGTH (ft.)
105	Reinforced Concrete Closed Web/Box Girder	LENGTH (ft.)
106	Other Closed Web/Box Girder	LENGTH (ft.)
107	Steel Open Girder/Beam	LENGTH (ft.)
109	Prestressed Concrete Open Girder/Beam	LENGTH (ft.)
110	Reinforced Concrete Open Girder/Beam	LENGTH (ft.)
111	Timber Open Girder/Beam	LENGTH (ft.)
112	Other Open Girder/Beam	LENGTH (ft.)
113	Steel Stringer	LENGTH (ft.)
115	Prestressed Concrete Stringer	LENGTH (ft.)
116	Reinforced Concrete Stringer	LENGTH (ft.)
117	Timber Stringer	LENGTH (ft.)
118	Other Stringer	LENGTH (ft.)
120	Steel Truss	LENGTH (ft.)
135	Timber Truss	LENGTH (ft.)
136	Other Truss	LENGTH (ft.)
141	Steel Arch	LENGTH (ft.)
142	Other Arch	LENGTH (ft.)
143	Prestressed Concrete Arch	LENGTH (ft.)
144	Reinforced Concrete Arch	LENGTH (ft.)
145	Masonry Arch	LENGTH (ft.)
146	Timber Arch	LENGTH (ft.)
147	Steel Main Cables	LENGTH (ft.)
148	Secondary Steel Cables	EACH
149	Other Secondary Cable	EACH
152	Steel Floor Beam	LENGTH (ft.)
154	Prestressed Concrete Floor Beam	LENGTH (ft.)
155	Reinforced Concrete Floor Beam	LENGTH (ft.)
156	Timber Floor Beam	LENGTH (ft.)
157	Other Floor Beam	LENGTH (ft.)
161	Steel Pin and Pin and Hanger Assembly or both	EACH
162	Steel Gusset Plate	EACH

Bearings (NBEs)		
El. No.	Element Name	Units
310	Elastomeric Bearing	EACH
311	Movable Bearing	EACH
312	Enclosed/Concealed Bearing	EACH
313	Fixed Bearing	EACH
314	Pot Bearing	EACH
315	Disk Bearing	EACH
316	Other Bearing	EACH

Substructures (NBEs)		
El. No.	Element Name	Units
202	Steel Column	EACH
203	Other Column	EACH
204	Prestressed Concrete Column	EACH
205	Reinforced Concrete Column	EACH
206	Timber Column	EACH
207	Steel Tower	LENGTH (ft.)
208	Timber Trestle	LENGTH (ft.)
210	Reinforced Concrete Pier Wall	LENGTH (ft.)
211	Other Pier Wall	LENGTH (ft.)
212	Timber Pier Wall	LENGTH (ft.)
213	Masonry Pier Wall	LENGTH (ft.)
215	Reinforced Concrete Abutment	LENGTH (ft.)
216	Timber Abutment	LENGTH (ft.)
217	Masonry Abutment	LENGTH (ft.)
218	Other Abutments	LENGTH (ft.)
219	Steel Abutment	LENGTH (ft.)
220	Reinforced Concrete Pile Cap/Footing	LENGTH (ft.)
225	Steel Pile	EACH
226	Prestressed Concrete Pile	EACH
227	Reinforced Concrete Pile	EACH
228	Timber Pile	EACH
229	Other Pile	EACH
231	Steel Pier Cap	LENGTH (ft.)
233	Prestressed Concrete Pier Cap	LENGTH (ft.)
234	Reinforced Concrete Pier Cap	LENGTH (ft.)
235	Timber Pier Cap	LENGTH (ft.)
236	Other Pier Cap	LENGTH (ft.)

Culverts (NBEs)		
El. No.	Element Name	Units
240	Steel Culvert	LENGTH (ft.)
241	Reinforced Concrete Culvert	LENGTH (ft.)
242	Timber Culvert	LENGTH (ft.)
243	Other Culvert	LENGTH (ft.)
244	Masonry Culvert	LENGTH (ft.)
245	Prestressed Concrete Culvert	LENGTH (ft.)

Reinforced Concrete - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Delamination / Spall / Patched Area (1080)	None.	Delaminated. Spall 1 in. or less deep or 6 in. or less in diameter. Patched area that is sound.	Spall greater than 1 in. deep or greater than 6 in. diameter. Patched area that is unsound or showing distress. Does not warrant structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Exposed Rebar (1090)	None.	Present without measurable section loss.	Present with measurable section loss, but does not warrant structural review.	
Efflorescence / Rust Staining (1120)	None.	Surface white without build-up or leaching without rust staining.	Heavy build-up with rust staining.	
Cracking* (1130)	Insignificant cracks or moderate width cracks that have been sealed.	Unsealed moderate width cracks or unsealed moderate pattern (map) cracking.	Wide cracks or heavy pattern (map) cracking.	
Abrasion / Wear (1190)	No abrasion or wearing.	Abrasion or wearing has exposed coarse aggregate but the aggregate remains secure in the concrete.	Coarse aggregate is loose or has popped out of the concrete matrix due to abrasion or wear.	
Distortion (1900)	None.	Distortion not requiring mitigation or mitigated distortion.	Distortion that requires mitigation that has not been addressed but does not warrant structural review.	
Settlement (4000)	None.	Exists within tolerable limits or arrested with no observed structural distress.	Exceeds tolerable limits but does not warrant structural review.	
Scour (6000)	None.	Exists within tolerable limits or has been arrested with effective countermeasures.	Exceeds tolerable limits, but is less than the critical limits determined by scour evaluation and does not warrant structural review.	
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Concrete Reinforcing Steel Protective Systems

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Effectiveness (3600)	Fully effective.	Substantially effective.	Limited effectiveness.	The protective system has failed or is no longer effective.
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Prestressed Concrete - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Delamination / Spall / Patched Area (1080)	None	Delaminated. Spall 1 in. or less deep or 6 in. or less in diameter. Patched area that is sound.	Spall greater than 1 in. deep or greater than 6 in. diameter. Patched area that is unsound or showing distress. Does not warrant structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Exposed Rebar (1090)	None	Present without measurable section loss.	Present with measurable section loss, but does not warrant structural review.	
Exposed Prestressing (1100)	None	Present without section loss	Present with section loss, but does not warrant structural review.	
Cracking* (1110)	Insignificant cracks or moderate width cracks that have been sealed.	Unsealed moderate width cracks or unsealed moderate pattern (map) cracking.	Wide cracks or heavy pattern (map) cracking.	
Efflorescence / Rust Staining (1120)	None	Surface white without build-up or leaching without rust staining.	Heavy build-up with rust staining.	
Abrasion / Wear (1190)	No abrasion or wearing	Abrasion or wearing has exposed coarse aggregate but the aggregate remains secure in the concrete.	Coarse aggregate is loose or has popped out of the concrete matrix due to abrasion or wear.	
Distortion (1900)	None	Distortion not requiring mitigation or mitigated distortion.	Distortion that requires mitigation that has not been addressed but does not warrant structural review.	
Settlement (4000)	None	Exists within tolerable limits or arrested with no observed structural distress.	Exceeds tolerable limits but does not warrant structural review.	
Scour (6000)	None	Exists within tolerable limits or has been arrested with effective countermeasures.	Exceeds tolerable limits, but is less than the critical limits determined by scour evaluation and does not warrant structural review.	
Damage (7000)	Not applicable	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

*The inspector should use judgment when utilizing the condition state defect definitions, especially for concrete cracking. The crack defect description definitions describe generalized distress, but the inspector should consider width, spacing, location, orientation, and structural or nonstructural nature of the cracking. The inspector should consider exposure and environment when evaluating crack width.

Reinforced Concrete: In general, cracks less than 0.012 inches can be considered insignificant, cracks ranging from 0.012 to 0.05 inches can be considered moderate, and cracks greater than 0.05 inches can be considered wide.

Prestressed Concrete: In general, cracks less than 0.004 inches can be considered insignificant, cracks ranging from 0.004 to 0.009 inches can be considered moderate, and cracks greater than 0.009 inches can be considered wide.

Pattern (Map) Cracking: Without further guidance, moderate is 1 ft. to 3 ft. spacing and heavy is less than 1 ft. spacing.

Wearing Surface - Condition State Definitions

Defect	CS 1 – Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Delamination / Spall / Patched Area / Pothole (3210)	None.	Delaminated. Spall less than 1 in. deep or less than 6 in. diameter. Patched area that is sound. Partial depth pothole.	Spall 1 in. deep or greater or 6 in. diameter or greater. Patched area that is unsound or showing distress. Full depth pothole.	The wearing surface is no longer effective.
Crack (3220)	Width less than 0.012 in. or spacing greater than 3.0 ft.	Width 0.012–0.05 in. or spacing of 1.0–3.0 ft.	Width of more than 0.05 in. or spacing of less than 1.0 ft.	
Effectiveness (3230)	Fully effective. No evidence of leakage or further deterioration of the protected element.	Substantially effective. Deterioration of the protected element has slowed.	Limited effectiveness. Deterioration of the protected element has progressed.	
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	

Bearings - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Corrosion (1000)	None.	Freckled Rust. Corrosion of the steel has initiated.	Section loss is evident or pack rust is present but does not warrant structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Connection (1020)	Connection is in place and functioning as intended.	Loose fasteners or pack rust without distortion is present but the connection is in place and functioning as intended.	Missing bolts, rivets, broken welds, fasteners or pack rust with distortion but does not warrant a structural review.	
Movement (2210)	Free to move.	Minor restriction.	Restricted but not warranting structural review.	
Alignment (2220)	Lateral and vertical alignment is as expected for the temperature conditions.	Tolerable lateral or vertical alignment that is inconsistent with the temperature conditions.	Approaching the limits of lateral or vertical alignment for the bearing but does not warrant a structural review.	
Bulging, Splitting or Tearing (2230)	None.	Bulging less than 15% of the thickness.	Bulging 15% or more of the thickness. Splitting or tearing. Bearing's surfaces are not parallel. Does not warrant structural review.	
Loss of Bearing Area (2240)	None.	Less than 10%.	10% or more but does not warrant structural review.	
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Joints - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Leakage (2310)	None.	Minimal. Minor dripping through the joint.	Moderate. More than a drip and less than free flow of water.	Free flow of water through the joint.
Seal Adhesion (2320)	Fully Adhered.	Adhered for more than 50% of the joint height.	Adhered 50% or less of joint height but still some adhesion.	Complete loss of adhesion.
Seal Damage (2330)	None.	Seal abrasion without punctures.	Punctured or ripped or partially pulled out.	Punctured completely through, pulled out, or missing.
Seal Cracking (2340)	None.	Surface crack.	Crack that partially penetrates the seal.	Crack that fully penetrates the seal.
Debris Impaction (2350)	No debris to a shallow cover of loose debris may be evident but does not affect the performance of the joint.	Partially filled with hard-packed material, but still allowing free movement.	Completely filled and impacts joint movement.	Completely filled and prevents joint movement.
Adjacent Deck or Header (2360)	Sound. No spall, delamination or unsound patch.	Edge delamination or spall 1 in. or less deep or 6 in. or less in diameter. No exposed rebar. Patched area that is sound.	Spall greater than 1 in. deep or greater than 6 in. diameter. Exposed rebar. Delamination or unsound patched area that makes the joint loose.	Spall, delamination, unsound patched area or loose joint anchor that prevents the joint from functioning as intended.
Metal Deterioration or Damage (2370)	None.	Freckled rust, metal has no cracks, or impact damage. Connection may be loose but functioning as intended.	Section loss, missing or broken fasteners, cracking of the metal or impact damage but joint still functioning.	Metal cracking, section loss, damage or connection failure that prevents the joint from functioning as intended.
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Concrete Protective Coating - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Wear (3510)	None.	Underlying concrete not exposed, coating showing wear from UV exposure, friction course missing.	Underlying concrete is not exposed, thickness of the coating is reduced.	Underlying concrete exposed, treated cracks are exposed.
Chalking (3520)	None.	Surface Dulling.	Loss of Pigment.	Not Applicable.
Peeling / Bubbling / Cracking (3530)	None.	Finish coats only.	Finish and primer coats.	Exposure of bare concrete.
Effectiveness (3540)	Fully effective.	Substantially effective.	Limited effectiveness.	The protective system has failed or is no longer effective.
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Steel - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Corrosion (1000)	None.	Freckled Rust. Corrosion of the steel has initiated.	Section loss is evident or pack rust is present but does not warrant structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Cracking (1010)	None.	Crack that has self arrested or has been arrested with effective arrest holes, doubling plates, or similar.	Identified crack exists that is not arrested but does not warrant structural review	
Connection (1020)	Connection is in place and functioning as intended.	Loose fasteners or pack rust without distortion is present but the connection is in place and functioning as intended.	Missing bolts, rivets, or fasteners; broken welds; or pack rust with distortion but does not warrant a structural review.	
Distortion (1900)	None.	Distortion not requiring mitigation or mitigated distortion.	Distortion that requires mitigation that has not been addressed but does not warrant structural review.	
Settlement (4000)	None.	Exists within tolerable limits or arrested with no observed structural distress.	Exceeds tolerable limits but does not warrant structural review.	
Scour (6000)	None.	Exists within tolerable limits or has been arrested with effective countermeasures.	Exceeds tolerable limits, but is less than the critical limits determined by scour evaluation and does not warrant structural review.	
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	

Steel Protective Coating - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Chalking (3410)	None.	Surface Dulling.	Loss of Pigment.	Not Applicable.
Peeling / Bubbling / Cracking (3420)	None.	Finish coats only.	Finish and primer coats.	Exposure of bare metal.
Oxide Film Degradation Color / Texture Adherence (weathering steel patina) (3430)	Yellow-orange or light brown for early development. Chocolate-brown to purple-brown for fully developed. Tightly adhered, capable of withstanding hammering or vigorous wire brushing.	Granular texture.	Small flakes, less than 1/2 in. diameter.	Dark black color. Large flakes, 1/2 in. diameter or greater or laminar sheets or nodules.
Effectiveness (3440)	Fully effective.	Substantially effective.	Limited effectiveness.	Failed, no protection of the underlying metal
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Timber - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Connection (1020)	Connection is in place and functioning as intended.	Loose fasteners or pack rust without distortion is present but the connection is in place and functioning as intended.	Missing bolts, rivets, broken welds, fasteners or pack rust with distortion but does not warrant a structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Decay / Section Loss (1140)	None.	Affects less than 10% of the member section.	Affects 10% or more of the member but does not warrant structural review.	
Check / Shake (1150)	Surface penetration less than 5% of the member thickness regardless of location.	Penetrates 5% - 50% of the thickness of the member and not in a tension zone.	Penetrates more than 50% of the thickness of the member or more than 5% of the member thickness in a tension zone. Does not warrant structural review.	
Crack (1160)	None.	Crack that has been arrested through effective measures.	Identified crack exists that is not arrested, but does not require structural review.	
Split / Delamination (1170)	None.	Length less than the member depth or arrested with effective actions taken to mitigate.	Length equal to or greater than the member depth, but does not require structural review.	
Abrasion / Wear (1180)	None or no measurable section loss.	Section loss less than 10% of the member thickness	Section loss 10% or more of the member thickness but does not warrant structural review.	
Distortion (1900)	None.	Distortion not requiring mitigation or mitigated distortion.	Distortion that requires mitigation that has not been addressed but does not warrant structural review.	
Settlement (4000)	None.	Exists within tolerable limits or arrested with no observed structural distress.	Exceeds tolerable limits but does not warrant structural review.	
Scour (6000)	None.	Exists within tolerable limits or has been arrested with effective countermeasures.	Exceeds tolerable limits, but is less than the critical limits determined by scour evaluation and does not warrant structural review.	
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	

Other Materials - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Corrosion (1000)	None.	Freckled Rust. Corrosion of the steel has initiated.	Section loss is evident or pack rust is present but does not warrant structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Cracking (1010)	None.	Crack that has self arrested or has been arrested with effective arrest holes, doubling plates, or similar.	Identified crack exists that is not arrested but does not warrant structural review.	
Connection (1020)	Connection is in place and functioning as intended.	Loose fasteners or pack rust without distortion is present but the connection is in place and functioning as intended.	Missing bolts, rivets, broken welds, fasteners or pack rust with distortion but does not warrant a structural review.	
Delamination / Spall / Patched Area (1080)	None.	Delaminated. Spall 1 in. or less deep or 6 in. or less in diameter. Patched area that is sound.	Spall greater than 1 in. deep or greater than 6 in. diameter. Patched area that is unsound or showing distress. Does not warrant structural review.	
Efflorescence / Rust Staining (1120)	None	Surface white without build-up or leaching without rust staining.	Heavy build-up with rust staining.	
Cracking** (1130)	Insignificant cracks or moderate width cracks that have been sealed.	Unsealed moderate width cracks or unsealed moderate pattern (map) cracking.	Wide cracks or heavy pattern (map) cracking.	
Deterioration (1220)	None.	Initiated breakdown or deterioration.	Significant deterioration or breakdown, but does not warrant structural review.	
Distortion (1900)	None.	Distortion not requiring mitigation or mitigated distortion.	Distortion that requires mitigation that has not been addressed but does not warrant structural review.	
Settlement (4000)	None.	Exists within tolerable limits or arrested with no observed structural distress.	Exceeds tolerable limits but does not warrant structural review.	
Scour (6000)	None.	Exists within tolerable limits or has been arrested with effective countermeasures.	Exceeds tolerable limits, but is less than the critical limits determined by scour evaluation and does not warrant structural review.	
Damage (7000)	Not applicable.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 4 under the appropriate material defect entry.

Masonry - Condition State Definitions

Defect	CS 1 - Good	CS 2 - Fair	CS 3 - Poor	CS 4 - Severe
Delamination / Spall / Patched Area (1080)	None.	Delaminated. Spall 1 in. or less deep or 6 in. or less in diameter. Patched area that is sound.	Spall greater than 1 in. deep or greater than 6 in. diameter. Patched area that is unsound or showing distress. Does not warrant structural review.	The condition warrants a structural review to determine the effect on strength or serviceability of the element or bridge; OR a structural review has been completed and the defects impact strength or serviceability of the element or bridge.
Efflorescence / Rust Staining (1120)	None.	Surface white without build-up or leaching without rust staining.	Heavy build-up with rust staining.	
Mortar Breakdown (1610)	None.	Cracking or voids in less than 10% of joints.	Cracking or voids in 10% or more of the of joints	
Split / Spall (1620)	None.	Block or stone has split or spalled with no shifting.	Block or stone has split or spalled with shifting but does not warrant a structural review.	
Patched Area (1630)	None.	Sound patch.	Unsound patch.	
Masonry Displacement (1640)	None.	Block or stone has shifted slightly out of alignment.	Block or stone has shifted significantly out of alignment or is missing but does not warrant structural review.	
Distortion (1900)	None.	Distortion not requiring mitigation or mitigated distortion.	Distortion that requires mitigation that has not been addressed but does not warrant structural review.	
Settlement (4000)	None.	Exists within tolerable limits or arrested with no observed structural distress.	Exceeds tolerable limits but does not warrant structural review.	
Scour (6000)	None	Exists within tolerable limits or has been arrested with effective countermeasures.	Exceeds tolerable limits, but is less than the critical limits determined by scour evaluation and does not warrant structural review.	
Damage (7000)	Not applicable	The element has impact damage. The specific damage caused by the impact has been captured in condition state 2 under the appropriate material defect entry.	The element has impact damage. The specific damage caused by the impact has been captured in condition state 3 under the appropriate material defect entry.	

**The inspector should use judgment when utilizing the condition state defect definitions, especially for cracking. The crack defect description definitions describe generalized distress, but the inspector should consider width, spacing, location, orientation, and structural or nonstructural nature of the cracking. The inspector should consider exposure and environment when evaluating crack width.
Other: In general, cracks less than 0.012 inches can be considered insignificant, cracks ranging from 0.012 to 0.05 inches can be considered moderate, and cracks greater than 0.05 inches can be considered wide.